



DuraFlash™

ME2 | SATA | 2.5" SSD

SMART's DuraFlash ME2 SATA 2.5" SSDs incorporate the latest generation 3D NAND-technology and SMART Modular's proprietary NVMSentry™ firmware to deliver high performance SSD products with endurance up to one drive writes per day (1 DWPD) for five years. The new ME2 SSDs offer better cost per bit over previous 64-layer and 96-layer NAND generations without sacrificing performance and reliability. Further optimization of the NVMSentry firmware also yields enhancements in read and write consistency over wide ranges of application workloads.

SMART's ME2 SATA 2.5" SSDs are available in both industrial and commercial temperature grades and have versions that implement SMART's SafeDATA™ power-loss, data-protection technology for graceful handling of power fluctuations and sudden power loss events.

Features & Benefits

- The Latest Generation 3D NAND Technology
- Quality of Service (QoS) with 3 Nines of Latency Consistency
- 1 DWPD For Five Years
- SMART's Proprietary NVMSentry Firmware
- SafeDATA Power-Loss, Data-Protection Technology
- TCG OPAL 2.0 and AES 256 Encryption
- End-to-End Data Path Protection
- Support I-Temp (-40°C to +85°C)

Product Family Overview

Form Factor	Capacity	Sequential Performance
2.5" SSD	240GB to 1920GB	
M.2 2242 SSD	240GB to 960GB	
M.2 2280 SSD	240GB to 1920GB	Up to 540MB/s Read
mSATA SSD	240GB to 1920GB	Up to 450MB/s Write
Slim SATA SSD	240GB to 1920GB	



Applications

- AI
- Data Center
- Industrial
- Networking
- Surveillance

Specifications

ME2 SATA 2.5" SSD	
NAND Type	eTLC
Performance	
Host Interface Rate (maximum)	SATA 3.0 6Gb/s
Capacities	240GB to 1920GB
Sequential Read (maximum)	Up to 540 MB/s
Sequential Write (maximum)	Up to 450 MB/s
Random Read (maximum)	Up to 90K IOPS
Random Write (maximum)	Up to 70K IOPS
Reliability	
MTBF	> 2,000,000 hours
Endurance (JEDEC Enterprise Workload) ¹	1920GB: 3330 TBW 960GB: 1671 TBW 480GB: 902 TBW 240GB: 513 TBW
DWPD	1
SafeDATA	Optional
Error Correction	LDPC
Data Security	
Encryption	AES-256, TCG OPAL 2.0
Power	
Input Voltage	VCC: 5 V ± 10%
Environmental	
Shock	1500 g half-sine, 0.5 msec, 1 shock along each axis, X, Y, Z in each direction
Vibration	20G rms 80-2000Hz, 1.52mm 20-80Hz, 3 axis
Operating Temperature	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
Storage Temperature	-40°C to +85°C
Humidity	40°C, Operation: 90% RH, Storage: 93% RH
Physical	
Length	100 mm
Width	69.85 mm
Height	7 mm

¹Endurance is directly related to the User Specific Workload.

Ordering Information

Part Number	Density
ME2 SATA 2.5" SSD	
Commercial Operating Temperature (0°C to +70°C)	
SRS251920FCM2BC2	1920GB
SRS25960GFCM2BC2	960GB
SRS25480GFCM2BC2	480GB
SRS25240GFCM2BC2	240GB
ME2 SATA 2.5" SSD	
Industrial Operating Temperature (-40°C to +85°C)	
SRS251920FIM2BC2	1920GB
SRS25960GFIM2BC2	960GB
SRS25480GFIM2BC2	480GB
SRS25240GFIM2BC2	240GB
ME2 SATA 2.5" SSD (SafeDATA)	
Commercial Operating Temperature (0°C to +70°C)	
SRS251920F1M2AC2	1920GB
SRS25960GF1M2AC2	960GB
SRS25480GF1M2AC2	480GB
SRS25240GF1M2AC2	240GB
ME2 SATA 2.5" SSD (SafeDATA)	
Industrial Operating Temperature (-40°C to +85°C)	
SRS251920F2M2AC2	1920GB
SRS25960GF2M2AC2	960GB
SRS25480GF2M2AC2	480GB
SRS25240GF2M2AC2	240GB



For more information, please visit: www.smartm.com

Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231
F: (+1) 510-623-1434 • E: info@smartm.com

Latin America:

T: (+55) 11 4417-7200 • E: sales.br@smartm.com

Asia/Pacific:

T: (+65) 6678-7670 • E: sales.asia@smartm.com

EMEA:

T: (+44) 0 7826-064-745 • E: sales.euro@smartm.com

Customer Service:

T: (+1) 510-623-1231 • E: customers@smartm.com