



## DuraFlash™

# R800 | SATA | 2.5" SSD

SMART's DuraFlash R800 SATA 2.5" solid state drives bring the advantages of non-volatile memory to embedded computing applications. The R800 are enterprise feature rich and reliable mass storage in a 2.5" SATA form factor available in both commercial and industrial temperature ranges.

SMART's R800 SATA 2.5" SSDs are offered with Triple-Level Cell (TLC) 3D NAND. The R800 product lines offer excellent sustained random read/write and sustained sequential read/write performance. The R800 is suitable for applications that cannot tolerate variations in performance.



### Features & Benefits

- Advanced Static and Dynamic Wear-Leveling
- Advanced Error Detection/Correction Circuitry for Superior Data Reliability
- Self-Monitoring Analysis and Reporting Technology (S.M.A.R.T.) Support
- Supports for 48bit LBA Addressing with Larger Maximum Transfer Size

### Product Family Overview

Capacity	Sequential Performance
<b>R800   SATA   2.5" SSD</b>	
480GB to 7680GB	Up to 550MB/s Read; Up to 530MB/s Write

### Applications

- ATCA Compute Blades
- Enterprise
- Distributed Scale-Out Cloud Servers
- Industrial Control
- NAS / SAN Storage Systems
- Single-Board Computers for Defense, Gaming and Industrial Control Applications
- Telecom and Networking Routers and Switches
- x86 Server-Storage Appliances

# Specifications

R800   SATA   2.5" SSD	
NAND Type	TLC
<b>Performance</b>	
Host Interface Rate (maximum)	6Gb/s (Backwards compatible to 3Gb/s & 1.5Gb/s)
Capacities	480GB to 7680GB
Sequential Read (maximum)	Up to 550MB/s
Sequential Write (maximum)	Up to 530MB/s
<b>Reliability</b>	
Data Reliability	< 1 Non-Recoverable Error in 10 <sup>17</sup> bits read
Data Retention	10 years >90% life remaining 1 year at the end of life
Endurance (JEDEC Enterprise Workload) <sup>1</sup>	7680GB: 5810 TBW 3840GB: 2905 TBW 1920GB: 1210 TBW 960GB: 595 TBW 480GB: 295 TBW
SafaDATA	Optional
Error Correction	LDPC (Equivalent to 130 bits/2KB)
<b>Environmental</b>	
Shock	1500 g half-sine, 0.5 msec, 1 shock along each axis, X, Y, Z in each direction
Vibration	20G 80-2000Hz, 1.52mm 20-80Hz, 3 axis
Operating Temperature	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
Storage Temperature	-40°C to +85°C
Humidity	40°C, Operation: 90% RH, Storage: 93% RH
Altitude	24,384 m [80,000 ft]
<b>Physical</b>	
Length	100 mm
Width	69.85 mm
Height	7.0 mm

<sup>1</sup>Endurance is directly related to the User Specific Workload.



For more information, please visit: [www.smartm.com](http://www.smartm.com)

## Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231  
F: (+1) 510-623-1434 • E: [info@smartm.com](mailto:info@smartm.com)

## Latin America:

T: (+55) 11 4417-7200 • E: [sales.br@smartm.com](mailto:sales.br@smartm.com)

## Asia/Pacific:

T: (+65) 6678-7670 • E: [sales.asia@smartm.com](mailto:sales.asia@smartm.com)

## EMEA:

T: (+44) 0 7826-064-745 • E: [sales.euro@smartm.com](mailto:sales.euro@smartm.com)

## Customer Service:

T: (+1) 510-623-1231 • E: [customers@smartm.com](mailto:customers@smartm.com)